



Product Datasheet

06 Downlights Fixed LED>The Chrome Bezel Range Aluminium

10124/W/C



24W SMD LED recessed downlight, chrome bezel range, IP44.

Complete with 600mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



238mm



125mm

Physical Specification


Item Group	06 Downlights Fixed LED
Family	The Chrome Bezel Range Aluminium
Order Code	10124/W/C
Colour	White
Material	Aluminium
Shape	Circular
Height	125mm
Diameter	238mm
Cutout Hole Diameter	210mm
Recessed Ceiling	Yes
Depth Required	160mm
Indoor	Yes

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	24W
IP Rating	IP44
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	600mA
Voltage	36V
Safety Class	
Power(Watts)	21,6W
IP Rating	IP44
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Sanan
LED Number	48
F Mark	F
Gear	

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	18-24W
Power Factor	0,9
Constant Current	Yes
600mA	30-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	50°
Operating Temp	80°
Housing Material	Plastic
Output Terminal	Cable
Brand	Kegu
Illumination Data	
Illumination Data	
Illumination Data Colour Temperature	4000K
	4000K 1550lm
Colour Temperature	
Colour Temperature Lumen Output	1550lm
Colour Temperature Lumen Output Light Efficiency	1550lm 64,58lm/W
Colour Temperature Lumen Output Light Efficiency CRI	1550lm 64,58lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	1550lm 64,58lm/W 80 120°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	1550lm 64,58lm/W 80 120°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	1550lm 64,58lm/W 80 120°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	1550lm 64,58lm/W 80 120°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	1550lm 64,58lm/W 80 120°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length	1550lm 64,58lm/W 80 120° \$\ill_{\text{1}}\$ 24,5cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	1550lm 64,58lm/W 80 120° 24,5cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height	1550lm 64,58lm/W 80 120° 24,5cm 24,5cm 12,5cm

Energy Label



Certification & Warranty

Warranty 2 Years

Weee Directive Yes

switch to one light!

