


OUTDOOR

ECLIPSE IP54 LED WALL LIGHT



	Height	Width	Depth
REL0630	86	160	100
REL1230	129	249	149

Codes:	REL0630-25	REL1230-25
Comparable to CFL(W):	11	18
Light Output L₁₀₀ (lm):	360	720
Beam Angle (deg):	120	120
Illuminance @ 1m (lx):	35	60
Colour Temp L₁₀₀ (k):	3,000	3,000
CRI L₁₀₀ (Ra):	80	80
Total Power Consumed (W):	6	12
Efficacy (lm/cctW):	60	60
Power Factor:	0.8	0.8
Rated LED life (hrs):	30,000	30,000
Ingress Protection (IP):	54	54
Ambient Operating Temp (°C):	-20<Ta<+50	-20<Ta<+50
Operating voltage (V):	100-240	100-240
Min Order Qty/Carton Qty:	1/12	1/8
Weight (Kg):	0.58	1.1
Warranty (yrs):	3	3

This superb looking fitting is manufactured from traditional high quality die cast aluminium with polycarbonate diffuser. It utilises state of the art LED technology to provide a great light output from a choice of wattages. It offers an attractive outdoor lighting solution with very low running costs and without the annoying failures associated with traditional light source lamps.

Surface mounted either as an up lighter or down lighter, these fittings are typically installed in domestic applications but can equally be used to excellent effect in sheltered housing outdoor common areas, hotel and restaurant or pub walkway applications without worry of burning if touched by children.

FEATURES	BENEFITS
<ul style="list-style-type: none"> Modern design Body manufactured from die cast aluminium with allen head type wall plate retaining machine screws Finished with a dark grey electrophoresis powder coating 	<ul style="list-style-type: none"> Great aesthetics with an individual look. Can be used for up or down lighter applications Strong and durable Exudes high quality and will not rust Long lasting finish which will look good for many years
<ul style="list-style-type: none"> Opal polycarbonate diffuser 	<ul style="list-style-type: none"> Provides a soft light with reduced glare Uniform light spread
<ul style="list-style-type: none"> Ingress protection to IP54 	<ul style="list-style-type: none"> Ideal for installation outdoors Ensures water or dust cannot enter the fitting so provides long life
<ul style="list-style-type: none"> Twin screw mounting wall plate 	<ul style="list-style-type: none"> Provides fast and simple mounting and access for electrical connection
<ul style="list-style-type: none"> Utilises high quality Runlite LED's to provide: <ul style="list-style-type: none"> High luminous flux Low power consumption High efficacy Long LED life 	<ul style="list-style-type: none"> Compared to traditional CFL & Incandescent light sources: <ul style="list-style-type: none"> Comparable light output Provides energy savings of over 40% Complies with Building Regulation efficacy requirement Last up to 20 times longer so no annoying lamp changes
<ul style="list-style-type: none"> High quality, high CRI warm white light 	<ul style="list-style-type: none"> Provides a warm subtle lighting ambience Good quality light is always available for peace of mind and security
<ul style="list-style-type: none"> Integral driver 	<ul style="list-style-type: none"> No separate enclosure required for power supply
<ul style="list-style-type: none"> No Infra-red or Ultra-violet in the light beam 	<ul style="list-style-type: none"> Is cool to touch so will not burn if touched
<ul style="list-style-type: none"> Robus 3 year warranty 	<ul style="list-style-type: none"> No internet registration or forms to fill in A quality energy efficient long life product Fit and forget – peace of mind

PLEASE NOTE – INFORMATION CONTAINED IN THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE